

Declaration of Performance No

226/1/CPR



| | |
|---|--|
| Unique identification code of the product-type: | ATLAS CERMIT BA-M (2020) |
| Intended use or uses: | Use on external walls, ceilings and columns. Use on internal walls, ceilings, columns and partition walls. |
| Manufacturer: | ATLAS sp. z o.o. ul. Jana Kilińskiego 2, 91-421 Łódź, Poland telefon: +48 (42) 631 89 45 www.atlas.com.pl |
| System or systems of assessment and verification of constancy of performance: | System 4 |
| Harmonized standard: | EN 998-1:2016 |

Declared performance:

| Essential characteristics | Performance |
|--|-----------------------------------|
| Reaction to fire | A1 |
| Water absorption | W _c 1 |
| Water permeability after required seasoning cycles | ≤ 1 ml/cm ² after 48 h |
| Water vapour permeability | μ ≤ 30 |
| Adhesion after required seasoning cycles | 0,3 N/mm ² FP:B |
| Thermal conductivity/Density | NPD |
| Durability | NPD |
| Dangerous substances | NPD |

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 01.09.2022.

ATLAS sp. z o.o.
Dyrektor ds. Jakości
Stasiak
Patrycja Stasiak