## Declaration of Performance No

## 125/3/CPR



Unique identification code of the product-type:	TYNK SILIKONOWO-SILIKATOWY ATLAS (2020)
Intended use or uses:	Use on external walls, ceilings and columns. Use on internal walls, ceilings, columns and partition walls
Manufacturer:	ATLAS sp. z o.o. ul. Jana Kilińskiego 2, 91-421 Łódź, Polska telefon: +48 (42) 631 89 45 www.atlas.com.pl
System or systems of assessment and verification of constancy of performance:	System 3
Harmonized standard:	EN 15824:2017 Notified body <b>No.0767 MPA Dresden GmbH</b>

## Declared performance:

Essential characteristics	Performance
Water vapour permeability	V <sub>1</sub>
Water absorption	W <sub>2</sub>
Adhesion	0,35 MPa
Durability	NPD
Thermal conductivity coefficient	NPD
Reaction to fire	A2-s1, d0
Dangerous substances	NPD

The performance of the product is in conformity with the declared performance range. This declaration of performance is issued in accordance to EU Regulation no. 305/2011 under sole responsibility of the manufacturer listed above.

Signed for and on behalf of the manufacturer by: Patrycja Stasiak in Łódź, 29.03.2022.

ATLAS sp. z o.o.

Dyrektor ds. Jakości

Staniez

Patrycja Stasiak